

HS 3540

Crystalyte europe



REAR WHEEL MOUNTING

Technical details

Motor type	Brushless direct drive
Output range	250 - 2000 Watt
Voltage range	24 - 48 Volt
Maximal Amp	45 Amp
RPM / V	10
Torque	40 - 80 Nm
Efficiency	86%
Weight	6,5 kg
Drop out	135 mm
Disc brake mounting	Yes
Freewheel mounting	Yes
Front or rear wheel	Rear wheel
Controller type	Sensorless and sensed controllers

Magnet width	35 mm
Poles	23 pair
Hall sensors	3 x Honeywell
Bearings	NSK industrial
Sealings	Yes
Motor phase plug	3 x Anderson PP45
Hall sensor plug	Mini XLR 5 pin

ALSO AVAILABLE WITH RIM & SPOKES

Spokes	SAPIM 125G INOX (size = 2,6 mm)
Rim	EXAL EX19 (24" - 29") / XL25 (20")
Rim sizes	20", 24", 26", 28" and 29er



AVAILABLE WITH
RIM & SPOKES



HS 3540


ORDER ONLINE
www.crystalyte-europe.com



Makes you want to drive electric


e-dr bvba • Hemelrijken 3a • 2890 Sint-Amands • Belgium • +32 (0)52 555 840 • info@crystalyte-europe.com

Measurements



Test results

Description	U	I	P1	M	N	P2	Eff
	(V)	(A)	(W)	(N.m)	(rpm)	(W)	(%)
Unload	35,94	0,918	33,00	0,04	250,0	1,04	3,1
Max-Eff	35,51	8,837	313,9	11,61	222,5	270,4	86,1
Max-Pout	34,87	25,41	886,5	37,04	170,7	661,9	74,6
Max-Torque	34,87	26,53	925,3	60,16	46,1	290,3	31,3
End	34,87	26,53	925,3	60,16	46,1	290,3	31,3



Speed table

